

The **Compact Series** of depositors are work horses and can be fitted with a full range of Unifiller accessories and attachments.

The Compact is available in four options:

- Compact Table Top FS
- Compact Mobile FS
- Compact Power Lift FS
- Dual (two Compacts on one frame)

Benefits:

- Small footprint
- Speed and portion accuracy
- Full wash down — all food contact parts dishwasher safe
- Tool free, quick cleaning and change-over design
- Deposit range — 0.25 oz (7 ml) 18 oz (530 ml)

Features:

- 5 product cylinder sizes available to meet your production requirements
- Stainless Steel design — Volumetric depositing
- Power Lift Model has a “one touch” system for raising and lowering of hopper
- The Mobile can be height adjusted manually
- Mobile and Power Lift have a 14 US Gallon (52 liter) conical hopper
- Table Top has a 6 US Gallon (23 liter) conical hopper

System includes:

- Removable work table
- Quick start guide & spare parts kit

COMPACT FILLER SERIES

3 Models for all Your Needs



1. 37in [94cm] x 15in [38cm]
28in [71cm]

2. 38in [97cm] x 28in [71cm]

3. 39in [98cm] x 28in [71cm]

33 - 68in [84 - 172cm] ADJUSTABLE
74in [187cm]

42 - 68in [106 - 172cm] ADJUSTABLE

1. Compact Table Top
2. Compact Mobile
3. Compact Power Lift

Product Cylinder Size	DEPOSIT VOLUME (fl oz)			
	Min. (15%)		Max.	
3"	2.7 oz	(80 ml)	18 oz	(530 ml)
2.5"	1.8 oz	(53 ml)	12 oz	(360 ml)
2"	1.1 oz	(32 ml)	7.6 oz	(225 ml)
1.5"	0.6 oz	(18 ml)	4.0 oz	(120 ml)
1"	0.25 oz	(7 ml)	1.7 oz	(50 ml)

Performance Specifications

 <p>Speed Up to 140 deposits/min (8400 deposits/hr) based on 20% volume and product consistency.</p>	 <p>Power Air: 4 CFM @ 80psi, 113 liters/minute @ 5.5 bar</p>
 <p>Volume 0.25 oz to 18 oz. 7ml to 530ml</p>	 <p>Particle Size Up to 3/4" cube 19mm</p>

Note: Equipment quoted is designed to run at the quoted speed and is dependent on operator efficiency, skill, deposit size and product consistency.

Shipping Information

Mobile / Power Lift:

- Dimensions: 36" x 30" x 52" (90 cm x 75 cm x 130 cm)
- Weight: 200 lbs. (91 kg)

Table Top:

- Dimensions: 23"x 22" x 26" (58 cm x 56 cm x 66 cm)
- Weight: 85 lbs (39 kg)

Unifiller Systems Inc. North America

Head Office Canada
Phone: (604) 940-2233
Email: info@unifiller.com
Website: www.unifiller.com

Unifiller Systems UK Ltd.

United Kingdom
Phone: 01604 499846
Email: customeruk@unifiller.com
Website: www.unifiller.com

Unifiller Systems Europe GmbH

Germany
Phone: +49 7621 583 6310
Email: info@unifiller-europe.com
Website: www.unifiller-europe.com

Product Configuration

Base Machine

	Standard
	NSF Standard

Hopper

	14 US Gal Conical Heated
	10 US Gal Cylindrical w Follower Plate

Product Cylinder

Hot kits for product temperatures of 140/180 °F

STD	Hot	Size
	NA	1"
		1.5"
		2"
		2.5"
		3"

Uni-Block

	Standard
	Extended Version
	Rotary Uni-Valve

Uni-Valve

	Standard
	Hot

Notes

Attachments – Handheld Nozzles

	Hand Held Nozzle 1"
	Hand Held Nozzle 1.5"
	Hand Held Nozzle 1.5" Rotary Cutoff

Attachments – Fixed Nozzles

	Drip Free Nozzle 1"
	Spot Depositor Kit
	Drip Free Nozzle 1.5"
	Rotary Cut-Off Nozzle
	Twin Injection Nozzle ¼ Short
	Twin Injection Nozzle ¼ Long
	Twin Injection Nozzle ⅜ Short
	Twin Injection Nozzle ⅜ Long
	Diving Nozzle 1.5"

Attachments - Other

Accessories

	Photo Sensor
	V-Block Centering Guide
	Hopper Stopper
	Portion / Fill Kit
	Preventative Maintenance Kit